



FASTFIT

T5 Series

External Power LED Tubes



SPECIFICATION DATA

Model:	T52 - 15	T54 - 15	T54 - 22	T54 - 30
LM79 Wattage @ 120VAC:	14.55	14.07	21.9	27.09
LM79 Lumens @ 5000K:	1764	1909	2577	3202
Lm/W:	121.24	135.68	119.13	117.35
DLC Rated Wattage @ 5000K:	14.54	16.3	21.77	27.87
DLC Rated Lumens @ 5000K:	1683	1778	2397	2961
CRI:	81.8	82.1	81.5	81.7
THD @ 120VAC:	8.69	7.79	8.29	8.05
DUV:	0.0008	0.0035	0.0009	0.0027
Power Supply*:	100-277VAC / External Mounted Class 2 / 0-10VDC Dimming & Non Dimming Option			
Lamp Base:	G5 Bi-Pin			
CCT Options:	3000K / 3500K / 4000K / 4500K / 5000K			
L70 Lifespan:	50,000 Hrs.			
Beam Angle / Field Angle	120° / 160°			
Length / Diameter:	23.825in / .629in (16mm)	47.165in / .629in (16mm)		
Weight:	.205lbs / 80g	.41lbs / 190g		
Operation Temperature:	10°C to +40°C Ambient			
Limited Warranty:	Standard 5-Year Limited Warranty / 10-Year Limited Warranty Option			

* Notes: Tested Values @ Ta=25°C All values are nominal. See Power Supply Spec. Sheet for Specifications and Configurations.

PART NUMBER SPECIFICATION			Part Number Example: FF-T54-A5-15-30-ND		
Series	Length / Series	Nominal Wattage	CCT Option	Dimming Option	Tube Finish
FASTFIT	T52 - A5 (2ft)	15 (15 Watts)	30 (3000K) 35 (3500K)	D (0-10VDC Dimming) ND (Non Dimming)	Blank (Frosted) CLR (Clear)
	T54 - A5 (4ft)	15 (15 Watts) 22 (22 Watts) 30 (30 Watts)	40 (4000K) 45 (4500K) 50 (5000K)		

PROJECT SPECIFICATION		
Project:	Part Numbers:	Quantity:
Approved:		
Date:		