

# LLW Linear

## W1 - Single Row Series



### SPECIFICATION SUMMARY

Model:	LLW-2-7-W1	LLW-3-12-W1	LLW-4-15-W1	LLW-5-20-W1	LLW-6-22-W1	LLW-8-30-W1
Wattage @120VAC:	7	12	15	20	22	30
Lumens @ 5000K:	840	1440	1800	2400	2640	3600
Lm / W:	≥120	≥120	≥120	≥120	≥120	≥120
Compliance Listings:	ETL	ETL	DLC / ETL	DLC / ETL	ETL	ETL
Length:	21.0in.	34.25in.	44.0in.	59.0in.	70.8in.	90.6in.
Width / Height:	1.12in x 1.51in					
CRI:	≥82					
THD @ 120VAC:	≤20					
Dimming Option:	Triac Dimming					
Voltage:	100-277VAC					
CCT Options:	3000K / 3500K / 4000K / 4500K / 5000K / 6000K					
Beam / Field Angle:	120°					
Power Factor:	≥92					
L70 Lifespan:	50,000 Hrs. (Rated)					
Operating Temp:	10°C to +40°C Ambient					
Construction:	Extruded Aluminum / Polycarbonate					
Ingress Protection:	IP65 Luminaire Body / IP65 Power Cable & Connectors					
Lens:	Frosted Polycarbonate					
L70 Lifespan:	50,000 Hrs.					
Standard Kit:	2 ea. Mount Clip / 1 ea. 10in Power Cable / 1 ea. 10in M-F Connector Cable					
Limited Warranty:	Standard 5-Year Limited Warranty / 10-Year Limited Warranty Option					

Notes: Values are nominal unless noted.

PART NUMBER SPECIFICATION						Part Number Example: LLW-15-W1-30-100277-ND-S	
LLW	-	-	- W1	-	- 100277		
Series	Model	Wattage	Series	CCT	Voltage:	Dimming Option:	Mounting Option:
	2 (2ft.)	7 (7 Watt)	W1 (Single Row LED Series)	30 (3000K) 35 (3500K) 40 (4000K) 45 (4500K) 50 (5000K)	100277 (100-277VAC)	D (Triac Dimming) ND (Non Dimming)	S (Standard Kit) M (Magnetic Mounts)
	3 (3ft.)	12 (12 Watt)					
	4 (4ft.)	15 (15 Watt)					
	5 (5ft.)	20 (20 Watt)					
	6 (6ft.)	22 (22 Watt)					
	8 (8ft.)	30 (30 Watt)					