



RCA Series

Parking Garage Luminaire



SPECIFICATION SUMMARY

Model: RCA - 45 RCA - 70

LM79 Lms @ 4000K:	4005.1	5703.3
LM79 Lms @ 5000K:	4149.6	5928.3
Wattage @ 120VAC:	43.67	68.73
Lm/W:	95.0	86.25
Voltage:	100 - 277VAC (Standard) 347VAC & 480VAC (Optional)	
Available CCT:	4000K / 5000K	
Optics:	IES Type 5 - Beam Angle 145° / Field Angle 177°	
CRI:	≥72	
Power Factor:	≥.97	
Dimming Option:	0-10VDC	
Control Sensor Option:	Dual Photo / Motion Programmable Step Dim	
L70 Lifespan:	≥50,000 hrs.	
Operating Temp:	-25°C - +40°C	
Ingress Protection:	UL Damp Location Rated	
Compliance:	DLC Outdoor Luminaire - Parking Garage / UL / cUL / RoHS	
Warranty:	5 Yr. Limited Warranty	
Dimensions (in):	9.57 x 9.57 x 3.07	

Notes: All values nominal. See Data Sheet for measured LM79 values.

PART NUMBER SPECIFICATION

Part Number Example: RCA - 45 - K2 - 40 - 100277 - D - NC

Series	Wattage	Model	CCT	Voltage	Dimming	Sensor Control
RCA Series Luminaire	45 (45 Watt) 70 (70 Watt)	K2	40 (4000K) 50 (5000K)	100277 (100-277VAC) 347 (347VAC) 480 (480VAC)	D (Dimming) ND (Non Dimming)	NC - No Control SM - Sensor Module

PROJECT SPECIFICATION

Project:	Part Numbers:	Quantity:
Approved:		
Date:		