



# TP Linear Luminaire

## IP 65 V1 Series



### SPECIFICATION SUMMARY

Model:	TP - 2 - 30	TP - 4 - 40	TP - 4 - 50
Wattage@120VAC:	29.4	39.8	50.5
DLC Rated Lumens:	2900	4100	5100
LM79 Lumens @ 4000K:	3165.80	4165.53	6253.95
Lm/W @ 5000K:	107.68	104.66	123.84
CRI:	85.5	85.3	85.7
Rated THD @ 120VAC:	<20	<20	<20
Rated Power Factor:	<.900	<.900	<.900
Compliance:	DLC 4.0 Linear Ambient (pending) / UL / cUL / RoHS		
CCT Options:	4000K / 5000K		
Length / Width / Height (in):	23.6 x 3.6 x 2.9		47.25 x 3.6 x 2.9
Voltage:	100 - 277VAC		
Beam / Field Angle:	118° / 160°		
Power Factor:	≥.99		
L70 Lifespan:	50,000 Hrs. (Rated)		
Operating Temp:	10°C to +50°C Ambient		
Standard Configuration:	2 Mounting Clips & Hard-wired Power Cable with IP65 Connector To 3.2ft. Bare Wire.		
Limited Warranty:	Standard 5-Year Limited Manufacturer's Warranty / Optional 10-Year Limited Warranty		

Notes: Values are nominal unless noted.

PART NUMBER SPECIFICATION								Part Number Example: TP-2-20-V1-100277-F- 30
TP -	-	-	- V1	- 100277	- F	-	-	-
Series	Length	Wattage	Model	Voltage	Lens Option	CCT Option	Emergency Pack Adder	Control Adder
	2 (2ft)	20 (20W) 30 (30 W)	V1	100277 (100- 277VAC)	F (Frosted)	40 (4000K) 50 (5000K)	Blank (No Pack) TPVBBU-2 (Factory Installed)	Blank (No Control)  D (0-1-V Dimming)
	4 (4ft)	40 (40W) 50 (50W)					Blank (No Pack) TPVBBU-4 (Factory Installed)	DALI (DALI Dimming)  TPVSM (Microwave Step / Photo)  TPVSMOF (Microwave On/Off)