

TP Linear Luminaire

IP 65 V2 Series



SPECIFICATION SUMMARY

Model:	TP - 2 - 20	TP - 2 - 30	TP - 4 - 40	TP - 4 - 50	TP - 5 - 50	TP - 5 - 60
LM79 Wattage @ 120VAC:	20.0	29.4	39.6	50.5	50.2	60.2
LM79 Lumens @ 5000K:	2200.0	3165.8	4904.0	6254.0	6000.0	7113.5
Lm/W:	110.0	107.68	123.84	123.84	119.52	118.16
CRI:	>80.0	82.5	83.0	81.4	>80.0	>80.0
THD @ 120VAC:	<20	10.93	10.82	11.29	<20	<20
DUV:	<.0050	.0035	.0028	.0036	<.0050	<.0050
Compliance:	UL / cUL	DLC / UL / cUL	DLC / UL / cUL	DLC / UL / cUL	UL / cUL	UL / cUL
CCT Options:	3000K / 3500K / 4000K / 4500K / 5000K / 6000K					
Length / Width / Height (in):	23.6 x 3.6 x 2.9		47.25 x 3.6 x 2.9		59.0 x 3.6 x 2.9	
Dimming Option:	10VDC					
Control Option:	Microwave On-Off / Microwave Step Dim - Photo					
Emergency BBU Option:	120min - 30% Illumination					
Voltage:	100 - 277VAC					
Beam / Field Angle:	118° / 160°					
Power Factor:	≥.99					
L70 Lifespan:	50,000 Hrs. (Rated)					
Standard Configuration:	2 Mounting Clips & Hard Wired Power Cable with IP65 Connector To 3.2ft. Bare Wire.					
Operating Temp:	-10°C to +50°C Ambient					
Limited Warranty:	Standard 5-Year Limited Warranty / 10-Year Limited Warranty Option					

Notes: Values are nominal unless noted.

PART NUMBER SPECIFICATION								Part Number Example: TP-2-20-V2-100277-F- 30
TP -	-	-	- V2	- 100277	-	-	-	-
Series	Length	Wattage	Model	Voltage	Lens Option	CCT Option	Emergency Pack Adder	Control Adder
	2 (2ft)	20 (20W) 30 (30 W)	V2	100277 (100- 277VAC)	F (Frosted) S (Striped)	30 (3000K) 35 (3500K) 40 (4000K) 45 (4500K) 50 (5000K) 60 (6000K)	Blank (No Pack) TPVBBU-2 (Factory Installed)	Blank (No Control)
	4 (4ft)	40 (40W) 50 (50W)					Blank (No Pack) TPVBBU-4 (Factory Installed)	D (0-1-V Dimming) DALI (DALI Dimming)
	5 (5ft)	50 (50W) 60 (60W)					Blank (No Pack) TPVBBU-5 (Factory Installed)	TPVSM (Microwave Step / Photo) TPVSMOF (Microwave On/Off)