



## SPECIFICATION SUMMARY

Model:	WP-NC-K3-30	WP-NC-K3-45	WP-NC-K3-70	WP-NC-K3-90	WP-NC-K3-135
Wattage @120VAC:	30	45	70	90	135
Lumens @ 5000K:	3400	4500	6800	9300	13800
Dimensions (W x H):	14.2 x 9.25in.			18.0 x 9.75in.	
Wall Projection:	7.4in.			8.75in	
Compliance Listings:	DLC (4.0 pending) / UL / cUL / RoHS				
CRI:	≥80				
Control:	Threaded Nipple Mount Photo Cell (sold as accessory) / PIR line voltage control compatible				
Voltage:	100-277VAC				
CCT Options:	4000K / 5000K				
Optics:	IES Type 4				
Power Factor:	≥98				
L70 Lifespan:	50,000 Hrs.				
Operating Temp:	-25°C to +40°C Ambient				
Construction:	Cast Aluminum / Polycarbonate / All Weather Polyester Paint Finish (Arch. Bronze)				
Ingress Protection:	IP65				
Limited Warranty:	Standard 5-Year Limited Manufacturer's Warranty / Optional 10-Year Limited Warranty				

Notes: All values are nominal unless indicated.

PART NUMBER SPECIFICATION			
WP - NC - K3 -	-	-	- 100277
Series	Wattage	CCT	Voltage:
	30 (30 Watt) 45 (45 Watt) 70 (70 Watt) 90 (90 Watt) 135 (135 Watt)	40 (4000K) 50 (5000K)	100277 (100-277VAC)

Part Number Example: WP - NC - K3 - 30 - 40 - 100277

PROJECT SPECIFICATION		
Project:	Part Numbers:	Quantity:
Approved:		
Date:		