



## External Power LED 2G11 BIAX



### SPECIFICATION DATA

Model:	T82 - A6 - 2G11 - 15
LM79 Wattage @ 120 VAC:	14.57
LM79 Lumens @ 5000K:	1739
Lm/W:	119.35
CRI:	82.4
THD @ 120VAC:	10.42
DUV:	0.0006
Approved Power Supply:	EXPS-15-A11 Series (See EXPS Power Supply Wattage Matrix for multiple tube configurations)
Power Supply Input:	100-277VAC
Connection / Lamp Base:	UL Type C / Single End / 2G11 4-pin
CCT Options:	3000K / 3500K / 4000K / 4500K / 5000K
L70 Lifespan:	>50,000hrs.
Beam Angle / Field Angle	118° / 160°
Length / Height / Width	21in / 1.125in / 1.5in
Weight:	6.5oz. / 185g
Operation Temperature:	-10°C to +40°C Ambient
Limited Warranty:	Standard 5-Year Limited Warranty / 10-Year Limited Warranty Option

Notes: Tested Values @ Ta = 25°C / All values are nominal.

PART NUMBER SPECIFICATION		Part Number Example: FF-T82-A6-2G11-15-30-ND		
FF -	- T82 - A6 - 2G11	- 15	-	-
Series	Length / Series	Nominal Wattage	CCT Option	Dimming Option
FASTFIT	T82 - A6 - 2G11 (2ft)	15 (15 Watts)	30 (3000K) 35 (3500K) 40 (4000K) 45 (4500K) 50 (5000K)	ND (Non Dimming) D (Dimming)

PROJECT SPECIFICATION		
Project:	Part Numbers:	Quantity:
Approved:		
Date:		