

CDL Commercial Series Retrofit LED Downlight

FEATURES & BENEFITS

- ▶ High efficiency retrofit for 4in / 6in / 8in / 10in recessed fixtures ranging from 14W to 54W in commercial ceiling or soffit applications.
- ▶ Cree® COB TrueWhite technology with >90 lm/w and >80CRI
- ▶ Damp location rated for enhanced application and installation flexibility.



TECHNICAL SPECIFICATIONS


Model	Retrofit Size	Wattage	Lumens	Dimming	CCT Option	Voltage	LED	CRI	Warranty	L70
CDL-4-E1-14	4in	14W	980	Non Dim	3000K/ 4000K/ 5000K	120VAC	Cree TrueWhite COB	>80	5 yrs.	50,000hrs
CDL-4-E1-27	4in	27W	1750	0-10VDC						
CDL-6-E1-18	6in	18W	1420							
CDL-6-E1-23	6in	23W	1723							
CDL-6-E1-27	6in	27W	1904							
CDL-8-E1-18	8in	18W	1420							
CDL-8-E1-23	8in	23W	1750							
CDL-8-E1-27	8in	27W	1960							
CDL-8-E1-23	8in	33W	2390							
CDL-8-E1-40	8in	40W	2540							
CDL-8-E1-54	8in	54W	3800							
CDL-10-E1-40	10in	40W	2715							
CDL-10-E1-54	10in	54W	3850							

Notes: Luminous flux ±3% / CCT ±175K @ Ta=25°C / CRI ±5% All values are nominal

Recommended Dimmer Types:

Leviton: AWRMG-7XX / AWSMG-7XX / AWSMT-7XX / IP710-LFZ/DLX - or equivalents.

Lutron: DIVA-DVTV / NOVA-NVTV / NOVAT_NTFTV / W/PP20 - or equivalents.



Model	A	B
CDL-4-E1-14	7.17in	5.59in
CDL-4-E1-27	7.17in	5.59in
CDL-6-E1-18	7.68in	7.48in
CDL-6-E1-23	7.68in	7.48in
CDL-6-E1-27	8.46	7.48in
CDL-8-E1-18	8.19in	9.29in

Model	A	B
CDL-8-E1-23	8.19in	9.29in
CDL-8-E1-27	8.98in	9.29in
CDL-8-E1-40	8.98in	9.29in
CDL-8-E1-54	9.76in	9.29in
CDL-10-E1-40	9.21in	10.98in
CDL-10-E1-54	10.00in	10.98in

PART NUMBER SPECIFICATION

CDL - - E1 -	-
Model	CCT Option
Model Designation (See Technical Specificaiton Table)	30 (3000K) 40 (4000K) 50 (5000K)