



# T5 Series

## External Power LED Tubes



► T5, Type C, LED Tube, externally driven with dual end power connection and suitable for interior and exterior use. Suitable for office, retail and food service.

► Reduces energy consumption up to 60%.

► Meets National Sanitation Foundation (NSF) standards.

### SPECIFICATION DATA

Model:	T52 - 15	T54 - 15	T54 - 22	T54 - 30
Wattage @ 120VAC:	14.5	15	22	30
Lumens @ 5000K:	>1680	>1950	>2800	>3750
Lm/W:	>115	>130	>125	>125
CRI:	>81	>82	>82	>82
THD @ 120VAC:	8.69	7.79	8.29	8.05
Power Supply*:	100-277VAC / External Mounted Class 2 / 0-10VDC Dimming & Non Dimming Option			
Lamp Base:	G5 Bi-pin			
CCT Options:	3500K / 4000K / 5000K			
L70 Lifespan:	50,000 Hrs.			
Beam Angle / Field Angle	120° / 160°			
Length / Diameter:	13.825in / .629in (16mm)	47.165in / .629in (16mm)		
Weight:	.205lbs / 80g	.41lbs / 190g		
Operation Temperature:	-20°C to +40°C Ambient			
Limited Warranty:	5 Year Limited Warranty			

Notes: Tested Values@Ta=25°C All values are nominal. See Power Supply Spec. Sheet for Specifications and Configurations.

PART NUMBER SPECIFICATION			Part Number Example: T52-A5-15-30-D		
T5 -		-	-	-	
Series	Length / Series	Nominal Wattage	CCT Option	Dimming Option	Tube Finish
T5 LED Tube	2 - A5 (2ft)	15 (15 Watts)	35 (3500K) 40 (4000K) 50 (5000K)	D (0-10VDC Dimming) ND (Non Dimming)	Blank (Frosted) CLR (Clear)
	4 - A5 (4ft)	15 (15 Watts) 22 (22 Watts) 30 (30 Watts)			

PROJECT SPECIFICATION		
Project:	Part Numbers:	Quantity:
Approved:		
Date:		