



**FASTFIT**

**Ballast Compatible / Line Voltage LED T8 2G11**



**SPECIFICATION DATA**

Model:	T82 - A2 - 2G11 - 15
LM79 Wattage @ 120 VAC:	14.57
LM79 Lumens @ 5000K:	1739
Lm/W:	119.35
DLC Rated Wattage @ 5000K:	NA
DLC Rated Lumens @ 5000K:	NA
CRI:	82.4
THD @ 120VAC:	10.42
DUV:	0.0006
Ballast Compatibility:	Approved Electronic Rapid Start / Instant Start / Programmed Start / Line Voltage Ballast Bypass
Connection / Lamp Base:	UL Type A & B / Single End / 2G11 4-pin
CCT Options:	3000K / 3500K / 4000K / 4500K / 5000K
L70 Lifespan:	>50,000hrs.
Beam Angle / Field Angle	118° / 160°
Length / Height / Width	21in / 1.125in / 1.5in
Weight:	6.5oz. / 185g
Operation Temperature:	-10°C to +40°C Ambient
Limited Warranty:	Standard 5-Year Limited Warranty / 10-Year Limited Warranty Option

Notes: Tested Values@ Ta=25°C / All values are nominal.

PART NUMBER SPECIFICATION		Part Number Example: FF-T82-A2-2G11-15-30	
FF -	- T82 - A2 - 2G11	- 15	-
Series	Length / Series	Nominal Wattage	CCT Option
FASTFIT	T82 - A2 - 2G11 (2ft)	15 (15 Watts)	30 (3000K) 35 (3500K) 40 (4000K) 45 (4500K) 50 (5000K)

**PROJECT SPECIFICATION**

Project:	Part Numbers:	Quantity:
Approved:		
Date:		