

Ballast Compatible / Line Voltage LED T8 UBend



SPECIFICATION DATA

Model:	T82 - A2 - UBend - 15
LM79 Wattage @ 120 VAC:	14.47
LM79 Lumens @ 5000K:	1879
Lm/W:	120.1
DLC Rated Wattage @ 5000K:	NA
DLC Rated Lumens @ 5000K:	NA
CRI:	81.4
THD @ 120VAC:	8.19
DUV:	0.0016
Ballast Compatibility:	Approved Electronic Rapid Start / Instant Start / Programmed Start / Line Voltage Ballast Bypass
Connection / Lamp Base:	UL Type A & B / Single End / G13 Bi-pin
CCT Options:	3000K / 3500K / 4000K / 4500K / 5000K
L70 Lifespan:	>50,000hrs.
Beam Angle / Field Angle	135°
Length / Height / Width	23.62in - 600mm / 1.02in - 26mm
Weight:	6.5oz. / 185g
Operation Temperature:	-10 °C to +40 °C Ambient
Limited Warranty:	Standard 5-Year Limited Warranty / 10-Year Limited Warranty Option

Notes: Tested Values@ Ta=25°C / All values are nominal.

PART NUMBER SPECIFICATION		Part Number Example: FF-T82Ubend-A2-6-15-30	
FF -	-	- 15	-
Series	Length / Series	Nominal Wattage	CCT Option
FASTFIT	T82Ubend - A2 - 6 (2ft / 6in gap) T82Ubend - A2 - 1625 (2ft / 1.625in gap)	15 (15 Watts)	30 (3000K) 35 (3500K) 40 (4000K) 45 (4500K) 50 (5000K)

PROJECT SPECIFICATION	
Project:	Part Numbers:
Approved:	
Date:	