

HBL iQ HL SWITCHABLE High Bay Series



SPECIFICATION DATA

HBL iQ HL SERIES	95/128		146/190		190/256		290/380	
Wattage Setting:	Low	High	Low	High	Low	High	Low	High
Rated Wattage @120VAC:	95	128	144	192	190	256	288	384
Rated Lumens @ 5000K:	13,200	17,000	19,750	25,500	26,400	36,000	41,000	51,000
Rated Lms / W:	138.9	132.8	137.2	132.8	136.8	132.8	137.2	132.8
L70 Lifespan (Hrs):	200,000	160,000	200,000	160,000	200,000	160,000	200,000	160,000
Weight:	10.9lbs		13.6lbs		21.8lbs		27.2lbs	
Dimensions (W x L x H)	9.5in x 27.5in x 3.5in				19in x 27.5in x 3.5in			
Listings:	DLC Premium - Indoor Luminaire High Bay (Pending) / UL / cUL / RoHS							
Optics Options:	Narrow (T1 VS - N7Hx6V - 112x67.6 Beam Angle) / Wide (T5S - N7Hx7V - 112x103 Beam Angle)							
Voltage:	100-277VAC Standard / 347VAC & 480VAC Factory Installed Adder							
Dimming & Control:	0-10VDC Dimming Standard / On - Off PIR & Step Dim PIR Factory Installed Adder							
THD@120VAC:	≤6%							
Power Factor@120VAC:	≥.99							
CCT:	5000K							
CRI:	≥84							
Operation Temperature:	-40C to +50C							
Limited Warranty:	Standard 5-Year Limited Warranty / 10-Year Limited Warranty Option.							

Notes: Luminous flux 10% / CCT ±175K / Data @ Ta=25°C / CRI ±5% All values are nominal.

PART NUMBER SPECIFICATION						
HBL-iQ HL	-	- 50	-	-	-	-
HBL-iQ HL	Wattage	CCT	Voltage	Optics	Control	Accessory Adders
HBL-iQ Switchable Series	95 - 128 146 - 190 190 - 256 290 - 380	50 (5000K)	100277 (100-277VAC) 347 (347VAC)	W (Wide) N (Narrow)	Blank (0-10 Dim Standard & No Sensor Control) iQ (Twist Lock Only) CiQOF (PIR On/Off Adder) CiQ (PIR Step Dim Adder)	Blank (No Accessory Adders) P7 (7ft Power Cord - Factory Installed) A7 (7ft Stainless Steel Suspension Kit) WG (Wire Guard - Factory Installed) LS (Lens Cover - Factory Installed)

PROJECT SPECIFICATION		
Project:	Quantity:	
Approved:		
Date:		