



LLW Linear

W2 - Double Row Series



- ▶ Fully integrated, double T5 fixtures suitable for office, retail and warehouse.
- ▶ Lead in wire; M-F connection or Seamless connection options.
- ▶ Replaces fluorescent NCF fittings.



SPECIFICATION SUMMARY

Model:	LLW-2-15-W2*	LLW-3-25-W2*	LLW-4-30-W2*
Wattage @120VAC:	15	25	30
Lumens @ 5000K:	>1800	>3000	>4000
Lm / W:	≥120	≥120	≥120
Length:	21.0in.	34.25in.	44.0in.
Width / Height:	1.38in x 1.60in		
CRI:	≥82		
THD @ 120VAC:	≤19		
Dimming Option:	Non-Dimming (Standard) / Triac Dimming (Special Order)		
Voltage:	100-277VAC		
CCT Options:	3500K / 4000K / 5000K		
Beam / Field Angle:	120°		
Power Factor:	≥95		
L70 Lifespan:	50,000 Hrs. (Rated)		
Operating Temp:	-20°C to +50°C Ambient		
Construction:	Extruded Aluminum / Polycarbonate		
Ingress Protection:	IP65 Luminaire Body / IP65 Power Cable & Connectors		
Lens:	Frosted Polycarbonate		
Compliance Listings:	DLC / UL / ETL		
Standard Kit:	2 ea. Mount Clip / 1 ea. 10in Power Cable / 1 ea. 10in M-F Connector Cable		
Limited Warranty:	Standard 5-Year Limited Warranty		

Notes: Values are nominal unless noted. * 5ft, 6ft & 8ft options available - Special order only. Call your eTech LED sales rep for details.

PART NUMBER SPECIFICATION						Part Number Example: LLW-2-15-W2-35-ND
LLW	-	-	- W2	-		
Series	Model	Wattage	Series	CCT	Dimming Option:	Mounting Option:
	2 (2ft.)	15 (15Watt)	W2 (2 Row LED Series)	35 (3500K) 40 (4000K) 50 (5000K)	ND (Non Dimming - Standard) D (Triac Dimming - Special Order)	Blank (Standard Kit) M (Magnetic Mounts)
	3 (3ft.)	25 (25Watt)				
	4 (4ft.)	30 (30Watt)				