

Ballast Compatible / Line Voltage LED T8 A2-UBend - Type A/B Lamp



SPECIFICATION DATA

Model: FF - T82UB - A2 - 15

Power:	Line Voltage 100-277VAC / Electronic Ballast Compatible*
Wattage @ 120 VAC:	15
Lumens @ 5000K:	>1950
Lm/W:	>130
CRI:	≥83
THD @ 120VAC:	<5%
Power Factor:	≥.9
Connection / Lamp Base:	UL Type A & B / Single End or Double End / G13 Bi-pin
CCT Options:	3500K / 4000K / 5000K
L70 Lifespan:	<68,000 hrs.
Beam Angle / Field Angle	120° / 160°
UBend Gap Option:	6 in (Standard) / 1.625 in **
Length / Height / Width	22 in / 7 in / 1.31 in
Weight:	.77 lbs
Operation Temperature:	-10°C to +40°C Ambient
Limited Warranty:	Standard 5 Year

Notes: Tested Values@ Ta=25°C / All values are nominal. *Refer to the A2UB Series approved ballast compatibility list. ** 1.625in gap UBends are not DLC Listed

PART NUMBER SPECIFICATION				Part Number Example: FF-T82UB-A2-15-35
FF -	-	- 15	-	-
Series	Length / Series	Nominal Wattage	CCT Option	UBend Gap Option
FASTFIT	T82UB - A2	15 (15 Watts)	35 (3500K) 40 (4000K) 50 (5000K)	Blank (6 in gap) 1625 (1.625 in gap)

PROJECT SPECIFICATION	
Project:	Part Numbers:
Approved:	
Date:	