



# Premium Volumetric Type Troffer TR-A9 Series



## SPECIFICATION DATA

Model:	TR - 22 - A9 - 25	TR - 22 - A9 - 30	TR - 22 - A9 - 36	TR - 24 - A9 - 25	TR - 24 - A9 - 36	TR - 24 - A9 - 40	TR - 24 - A9 - 50
Wattage:	24.8	30	36	25	35.9	38.5	50
Lumens:	>3340	>3800	>5000	>3200	>4950	>5050	>6300
Lm/W @ 5000K:	>135	>125	>135	>125	>135	>130	>125
CRI:	>84	>82	>83	>82	>84	>81	>82
THD @ 120VAC:	10.93	10.93	10.82	≤15	11.39	11.29	11.30
Voltage Options:	100 - 277VAC						
CCT Options:	3500K / 4000K / 5000K						
Beam / Field Angle:	120° / 168°						
Power Factor:	≥.99						
L70 Lifespan:	50,000 Hrs. / 66,000 Hrs. L70 (ISTMT & TM-21)						
Operating Temp:	-30°C to +40°C Ambient						
Compliance:	DLC / Damp Location UL / RoHS						
Limited Warranty:	Standard 5-Year Limited Warranty						
Max. Dimensions (in):	23.74 x 23.74 x 3.66in			47.64 x 23.74 x 3.66in			
Total System Weight:	≤4lbs		≤5lbs		≤10lbs		

Notes: Values are nominal unless noted.

## PART NUMBER SPECIFICATION

Part Number Example: TR-22-A9-25-35-D

TR	-	-	-	- D
Series	Model	Wattage	CCT	Dimming
	22-A9 (2 x 2ft.)	25 (25 Watt) 30 (30 Watt) 36 (36 Watt)	35 (3500K) 40 (4000K) 50 (5000K)	D (0-10V Dimming)
	24-A9 (2 x 4ft.)	25 (25 Watt) 36 (36 Watt) 40 (40 Watt) 50 (50 Watt)		

## PROJECT SPECIFICATION

Project:	Part Numbers:	Quantity:
Approved:		