



# LED Wallpack

## Full-Cutoff / Dark Sky Compliant

### SPECIFICATION FEATURES & BENEFITS

- Suitable for both indoor and outdoor application, also suitable for J-BOX mounting and surface mounting
- Optional Photocell allows for security and energy savings



### SPECIFICATION SUMMARY

Model:	WPF45W27V50KD	WPF70W27V50KD	WPF90W27V50KD	WPF135W27V50KD
Wattage @120VAC:	45	70	90	135
Lumens @ 5000K:	4900	7350	8500	13,000
Dimensions (W x H):	14.2 x 8.75in.		18.0 x 9.75in.	
Wall Projection:	9.25in.		10.8in	
Compliance Listings:	DLC / UL / RoHS			
CRI:	≥80			
Control:	Threaded Nipple Mount Photo Cell (sold as accessory) / PIR line voltage control compatible			
Voltage:	100-277VAC Standard or 347-480V Optional			
CCT Options:	5000K			
Optics:	IES Type 3			
Power Factor:	≥98			
L70 Lifespan:	50,000 Hrs.			
Operating Temp:	-25°C to +40°C Ambient			
Construction:	Cast Aluminum / Polycarbonate / All Weather Polyester Paint Finish (Arch. Bronze)			
Ingress Protection:	IP65 / Wet Location			
Limited Warranty:	Standard 5 Year Warranty			

Notes: All values are nominal unless indicated.

### PART NUMBER SPECIFICATION

Part Number Example: WPF30W27V50KD

WPF	-	-	50K	D	-
Series	Wattage	Voltage	CCT	Finish	Options
Full Cut-off Wall Pack Manufacturer: Mester LED Lighting	45W (45 Watt) 70W (70 Watt) 90W (90 Watt) 135W (135 Watt)	27V (100-277V) 48V (347-480V)	50K (5000K)	D (Dark Bronze)	Blank (Without Photocell) P0 (120-277V Photocell) P1 (120V Photocell) P2 (277V Photocell)

### PROJECT SPECIFICATION

Project:	Part Numbers:	Quantity:	
Approved:			
Date:			