



# LED Wallpack Standard Non-Cutoff

## SPECIFICATION FEATURES & BENEFITS

- ▶ Suitable for both indoor and outdoor application, also suitable for J-BOX mounting and surface mounting
- ▶ Optional Photocell allows for security and energy savings



## SPECIFICATION SUMMARY

Model:	WP30W27V50KD	WP45W27V50KD	WP70W27V50KD	WP90W27V50KD	WP135W27V50KD
Wattage @120VAC:	30	45	70	90	135
Lumens @ 5000K:	3400	5300	8100	11,200	16,400
Dimensions (W x H):	14.2 x 9.25in.			18.0 x 9.75in.	
Wall Projection:	7.4in.			8.75in	
Compliance Listings:	DLC / UL / RoHS				
CRI:	≥80				
Control:	Threaded Nipple Mount Photo Cell (sold as accessory) / PIR line voltage control compatible				
Voltage:	100-277VAC				
CCT Options:	5000K				
Optics:	IES Type 4				
Power Factor:	≥98				
L70 Lifespan:	50,000 Hrs.				
Operating Temp:	-40°C to +40°C Ambient				
Construction:	Cast Aluminum / Polycarbonate / All Weather Polyester Paint Finish (Arch. Bronze)				
Ingress Protection:	IP65 / Wet Location				
Limited Warranty:	Standard 5 Year Limited Warranty				

Notes: All values are nominal unless indicated.

## PART NUMBER SPECIFICATION

Part Number Example: W73027V50K

WP	-	27V	50	D	-
Series	Wattage	Voltage	CCT	Finish	Options
Non Cut-off Wall Pack Manufacturer: Mester LED Lighting	30 (30 Watt) 45 (45 Watt) 70 (70 Watt) 90 (90 Watt) 135 (135 Watt)	27V (100-277V)	50KD (5000K)	D (Dark Bronze)	Blank Without Photocell P1 120V Photocell P2 277V Photocell

## PROJECT SPECIFICATION

Project:	Part Numbers:		Quantity:
Approved:			
Date:			