



SPECIFICATION SUMMARY

Model:	WP-FC-K3-45	WP-FC-K3-70	WP-FC-K3-90	WP-FC-K3-135
Wattage @ 120VAC:	45	70	90	135
Lumens @ 5000K:	4900	7350	8500	13,000
Dimensions (W x H):	14.2 x 8.75in.		18.0 x 9.75in.	
Wall Projection:	9.25in.		10.8in	
Compliance Listings:	DLC (4.0 pending) / UL / cUL / RoHS			
CRI:	≥80			
Control:	Threaded Nipple Mount Photo Cell (sold as accessory) / PIR line voltage control compatible			
Voltage:	100-277VAC			
CCT Options:	4000K / 5000K			
Optics:	IES Type 3			
Power Factor:	≥98			
L70 Lifespan:	50,000 Hrs.			
Operating Temp:	-25°C to +40°C Ambient			
Construction:	Cast Aluminum / Polycarbonate / All Weather Polyester Paint Finish (Arch. Bronze)			
Ingress Protection:	IP65			
Limited Warranty:	Standard 5-Year Limited Warranty / 10-Year Limited Warranty Option			

Notes: All values are nominal unless indicated.

PART NUMBER SPECIFICATION			Part Number Example: WP - FC - K3 - 30 - 40 - 100277
WP - FC - K3 -	-	-	- 100277
Series	Wattage	CCT	Voltage:
	45 (45 Watt) 70 (70 Watt) 90 (90 Watt) 135 (135 Watt)	40 (4000K) 50 (5000K)	100277 (100-277VAC)

PROJECT SPECIFICATION		
Project:	Part Numbers:	Quantity:
Approved:		
Date:		